# NSN 5315-01-242-1353

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-242-1353

## Shank Diameter:

Between 0.9940 inches and 0.9990 inches

## **Button Handle Diameter:**

2.200 inches

# **Detent Quantity:**

2

## Actuation Method:

Push button

#### Grip Length:

Between 4.600 inches and 4.620 inches

## **Actuation Type:**

Pull and push

## Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

## Shear Strength:

131000 double pounds per square inch

## Shoulder To Head End Distance:

2.160 inches

## Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

1.000 inches

# **Special Features:**

Can also be furnished with four detents

#### Material:

Steel comp 4130 spindle

## **Material Specification:**

Mil-s-6758 military specification single material response spindle

## Surface Treatment:

Cadmium spindle and chromate spindle

## Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response spindle

#### Style Designator:

Button

## **Specification Data:**

80205-nas1343 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5315-01-242-1353

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

