

View Online at <https://aerobasegroup.com/nsn/5315-01-242-7788>

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Button Handle Diameter:

Between 0.875 inches and 1.135 inches

Detent Quantity:

2

Lanyard Length:

Between 8.750 inches and 9.250 inches

Actuation Method:

Push button

Grip Length:

Between 1.900 inches and 1.920 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

18400 double pound

Shoulder To Head End Distance:

1.040 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.365 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 1 cl 3 federal specification 1st treatment response spindle or qq-p-416 type 2 cl 3 federal specification 2nd treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.