NSN 5315-01-243-5209

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-243-5209 **Head Diameter:** 0.310 inches **Shank Diameter:** Between 0.1870 inches and 0.1885 inches **Ring Handle Diameter:** 1.060 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 0.600 inches and 0.620 inches **Actuation Type:** Push **Hardness Rating:** 58.0 rockwell c detent and 62.0 rockwell c detent **Shear Strength:** 4600 double pounds per square inch **Shoulder To Head End Distance:** 0.730 inches Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.230 inches and 0.260 inches Material: Steel head **Material Specification:** Qq-s-763 federal specification single material response detent **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 1 or 2, cl 2 federal specification single treatment response spindle **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A212a0

NSN 5315-01-243-5209

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.