

View Online at <https://aerobasegroup.com/nsn/5315-01-243-9040>

**Head Diameter:**

Between 0.6100 inches and 0.6400 inches

**Shank Diameter:**

Between 0.4950 inches and 0.4980 inches

**Ring Handle Diameter:**

1.1870 inches

**Detent Quantity:**

2

**Actuation Method:**

Handle

**Grip Length:**

Between 2.5000 inches and 2.5200 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shear Strength:**

34900 double pounds per square inch

**Shoulder To Head End Distance:**

0.5625 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.5156 inches

**Material:**

Steel spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Cadmium spring

**Surface Treatment Specification:**

Qq-p-416 ty1 or ty2 cl 3 federal specification single treatment response shank

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.