

View Online at <https://aerobasegroup.com/nsn/5315-01-243-9219>

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Detent Quantity:**

2

**Lanyard Length:**

6.000 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 1.2000 inches and 1.2200 inches

**Actuation Type:**

Push

**Hardness Rating:**

58.0 rockwell c detent and 62.0 rockwell c detent

**Shoulder To Head End Distance:**

1.450 inches

**Pin Center To Handle End Distance:**

1.730 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.370 inches and 0.400 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Qq-s-763 federal specification single material response detent

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response shank and qq-p-35 federal specification single treatment response shank

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.