## NSN 5315-01-243-9560

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-243-9560

| First End Style:  |
|---|
| Square  |
| Overall Length:   |
| 3.150 inches  |
| Diameter:   |
| Between 0.581 inches and 0.586 inches   |
| Effective Length:   |
| 1.470 inches  |
| Undercut Diameter:  |
| Between 0.109 inches and 0.111 inches   |
| Undercut Width:   |
| 1.080 inches  |
| Undercut Radius:  |
| 0.250 inches  |
| Hole Arrangement Style:   |
| Both end drilled  |
| First Hole Diameter:  |
| 0.250 inches  |
| Second Hole Diameter:   |
| 0.250 inches  |
| Distance From Centerline Of Hole To End Of Pin:   |
| 0.350 inches  |
| Center To Center Distance Between Holes:  |
| 2.450 inches  |
| Second End Relationship With First End:   |
| Identical   |
| Hardness Rating:  |
| 35.0 rockwell c and 37.0 rockwell c   |
| First End Location:   |
| Long end  |
| Special Features:   |
| 0.094 in. Min and 0.097 in. Maximum hole 2.000 in. From centerline of hole to second end of pin |
| Material:   |
| Steel comp 630  |
| Material Specification:   |
| Ams 5643 cond a assn standard single material response  |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35, type 1, or 2, or 3 federal specification single treatment response                     |
| Style Designator:   |
| Groove  |

## NSN 5315-01-243-9560

Headless Grooved Pin - Page 2 of 2



| C | ha  | Ιf | 1 | ife   |  |
|---|-----|----|---|-------|--|
| • | ııe |    | _ | .II C |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0