NSN 5315-01-244-4718

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-244-4718 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.430 inches **Shank Length:** 0.410 inches **Shoulder Width Across Flats:** 0.500 inches **Shank Diameter:** Between 0.249 inches and 0.250 inches **Overall Length:** 0.900 inches First End Taper Length: 0.050 inches **Second End Taper Length:** 0.220 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** 0.250 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Second End Tip Radius:** 0.060 inches **Second Shank Length:** 0.490 inches Material: Steel comp 302 **Material Specification:**

Mil-s-7720, cond b military specification single material response

Surface Treatment:

Cadmium and chromate

NSN 5315-01-244-4718

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment Spec | ific | ation: |
|------------------------|------|--------|
|------------------------|------|--------|

Qq-p-416 ty2 cl2 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7720 spec.