

View Online at <https://aerobasegroup.com/nsn/5315-01-246-9868>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.580 inches and 0.620 inches

**Shank Length:**

Between 1.365 inches and 1.385 inches

**Washer Outside Diameter:**

Between 0.410 inches and 0.450 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Overall Length:**

Between 1.965 inches and 1.985 inches

**Material Thickness:**

Between 0.115 inches and 0.135 inches

**Shank Length Under Washer:**

Between 1.240 inches and 1.260 inches

**Material For Which Designed:**

Concrete or concrete, extra hard or masonry or steel

**Thread Size:**

0.250 inches

**Material:**

Steel comp 302 or steel comp 303

**Material Specification:**

Qq-a-764 federal specification all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072-e300 military specification single treatment response

**Style Designator:**

Guided or powder actuated

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-f-14072-e300 spec.