## NSN 5315-01-249-2905

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-249-2905 **Head Diameter:** 0.950 inches **Shank Diameter:** Between 0.4970 inches and 0.4995 inches **Ring Handle Diameter:** 1.348 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 2.300 inches and 2.320 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c shank Shear Strength: 36900 double pound **Shoulder To Head End Distance:** 1.580 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.530 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1338 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5315-01-249-2905

Quick Release Pin - Page 2 of 2



Fiig:

A212a0