## NSN 5315-01-249-3160

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-249-3160 **Head Diameter:** 2.120 inches **Shank Diameter:** Between 0.9970 inches and 0.9985 inches **Ring Handle Diameter:** 1.640 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.500 inches and 1.520 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle Shear Strength: 147000 double pounds per square inch **Shoulder To Head End Distance:** 2.000 inches Pin Attachment Type: Ring and hook **Detent To Tapered End Distance:** Between 0.860 inches and 0.890 inches Material: Steel comp 630 spindle or steel, comp ph 15-7 m0 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1343 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5315-01-249-3160

Quick Release Pin - Page 2 of 2



Fiig:

A212a0