## NSN 5315-01-249-7679

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-249-7679 **Head Diameter:** 0.800 inches **Handle Length:** 2.750 inches **Shank Diameter:** Between 0.4335 inches and 0.4350 inches **Detent Quantity:** 2 Lanyard Length: Between 9.750 inches and 10.250 inches **Actuation Method:** Push button **Grip Length:** 1.250 inches **Actuation Type:** Push **Shoulder To Head End Distance:** 3.200 inches Pin Attachment Type: Cable lanyard w/terminations **Detent To Tapered End Distance:** Between 0.350 inches and 0.380 inches **Special Features:** Flats ea side of shank to 0.370 in. Min and 0.374 in. Maximum across flats Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response spindle **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Unit Of Measure:
-Demilitarization:
No
Fiig:
A212a0

## NSN 5315-01-249-7679

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.