NSN 5315-01-254-0223

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-254-0223 First End Style: Chamfered **Second End Style:** Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.405 inches **Shank Length:** 1.468 inches **Shoulder Width Across Flats:** 0.125 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Overall Length:** Between 2.091 inches and 2.095 inches First End Taper Length: 0.030 inches **Second End Taper Length:** Between 0.248 inches and 0.252 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:**

0.250 inches

Second Shank Diameter:

Between 0.2490 inches and 0.2495 inches

First End Location:

Chamfered end

First End Taper Angle:

45.0 degrees

Second End Tip Radius:

Between 0.060 inches and 0.090 inches

Second Shank Length:

Between 0.498 inches and 0.502 inches

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

NSN 5315-01-254-0223

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0