NSN 5315-01-254-0224

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-254-0224

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.530 inches
Shoulder Width Across Flats:
0.125 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Overall Length:
Between 1.153 inches and 1.157 inches
First End Taper Length:
0.030 inches
Second End Taper Length:
Between 0.248 inches and 0.252 inches
Thready Qty Per Inch (tpi):
28
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
Second Shank Diameter:
Between 0.2490 inches and 0.2495 inches
First End Location:
Chamfered end
First End Taper Angle:
45.0 degrees
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
Between 0.123 inches and 0.127 inches
Material:

Material Specification:

Steel comp xm-13

Ams5629 assn standard single material response

NSN 5315-01-254-0224

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0