## NSN 5315-01-254-0225

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-254-0225

First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.405 inches Shank Length: 0.718 inches **Shoulder Width Across Flats:** 0.125 inches Shank Diameter: Between 0.2490 inches and 0.2495 inches **Overall Length:** Between 1.341 inches and 1.345 inches First End Taper Length: 0.030 inches Second End Taper Length: Between 0.248 inches and 0.252 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Second Shank Diameter: Between 0.2490 inches and 0.2495 inches **First End Location:** Chamfered end First End Taper Angle: 45.0 degrees Second End Tip Radius: Between 0.060 inches and 0.090 inches Second Shank Length: Between 0.498 inches and 0.502 inches Material: Steel comp xm-13 **Material Specification:** 

Ams5629 assn standard single material response

## NSN 5315-01-254-0225

Headless Shoulder Pin - Page 2 of 2

Surface Treatment:

Passivate

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

