# NSN 5315-01-254-6452

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-254-6452

## Shank Diameter:

Between 0.5595 inches and 0.5610 inches

#### **Button Handle Diameter:**

Between 1.340 inches and 1.650 inches

## **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 1.300 inches and 1.320 inches

#### Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

46000 double pound

## Shoulder To Head End Distance:

1.410 inches

## Pin Attachment Type:

Link or ring

## Detent To Tapered End Distance:

Between 0.480 inches and 0.510 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

Button

Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A212a0