

View Online at <https://aerobasegroup.com/nsn/5315-01-255-2267>

**Head Diameter:**

Between 0.600 inches and 0.800 inches

**Shank Diameter:**

Between 0.497 inches and 0.498 inches

**Ring Handle Diameter:**

1.160 inches

**Detent Quantity:**

2

**Lanyard Length:**

7.000 inches

**Actuation Method:**

Push button

**Grip Length:**

2.300 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

32800 double pounds per square inch

**Shoulder To Head End Distance:**

1.140 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Passivate ring

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response spring

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.