

View Online at <https://aerobasegroup.com/nsn/5315-01-255-4743>

**Head Diameter:**

Between 0.720 inches and 0.780 inches

**Handle Length:**

Between 2.250 inches and 2.500 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 7.750 inches and 8.250 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 5.400 inches and 5.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.820 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.530 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification 1st material response shank and mil-s-6758 military specification 2nd material response shank

**Surface Treatment:**

Cadmium spindle

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.