## NSN 5315-01-255-5104

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-255-5104 **Head Diameter:** 0.750 inches **Shank Diameter:** Between 0.1870 inches and 0.1895 inches **Ring Handle Diameter:** 1.223 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.600 inches and 1.620 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c shank Shear Strength: 5150 double pound **Shoulder To Head End Distance:** 1.490 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 630 spindle or steel comp 632 spindle **Material Specification:** Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle **Surface Treatment:** Passivate spindle **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response spindle **Style Designator:** Ring handle **Specification Data:** 80205-nas1333 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5315-01-255-5104

Quick Release Pin - Page 2 of 2



Fiig:

A212a0