NSN 5315-01-256-0485

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-256-0485

Shank Diameter:

Between 0.2470 inches and 0.2495 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.800 inches and 0.820 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

8200 double pound

Shoulder To Head End Distance:

1.550 inches

Pin Center To Handle End Distance:

1.780 inches

Pin Attachment Type:

Ring or hook

Detent To Tapered End Distance:

0.380 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

Style Designator:

L handle

Specification Data:

80205-nas1334 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

NSN 5315-01-256-0485

Quick Release Pin - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

