

View Online at <https://aerobasegroup.com/nsn/5315-01-256-0485>

**Shank Diameter:**

Between 0.2470 inches and 0.2495 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.800 inches and 0.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shear Strength:**

8200 double pound

**Shoulder To Head End Distance:**

1.550 inches

**Pin Center To Handle End Distance:**

1.780 inches

**Pin Attachment Type:**

Ring or hook

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

L handle

**Specification Data:**

80205-nas1334 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.