NSN 5315-01-257-6184

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-257-6184 **Shank Diameter:** Between 0.1870 inches and 0.1896 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 1.500 inches and 1.520 inches **Actuation Type:** Push Hardness Rating: 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 4600 double pound **Shoulder To Head End Distance:** 1.580 inches Pin Center To Handle End Distance: 1.780 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium spindle and chromate spindle **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response spindle **Style Designator:** L handle **Specification Data:** 80205-nas1333 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

NSN 5315-01-257-6184

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.