NSN 5315-01-257-9843

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-257-9843

| Shank Diameter: |
|--|
| Between 0.3095 inches and 0.3110 inches |
| Button Handle Diameter: |
| Between 0.810 inches and 1.135 inches |
| Detent Quantity: |
| 2 |
| Actuation Method: |
| Push button |
| Grip Length: |
| Between 2.400 inches and 2.420 inches |
| Actuation Type: |
| Pull |
| Shear Strength: |
| 14400 double pounds per square inch |
| Shoulder To Head End Distance: |
| 0.930 inches |
| Pin Attachment Type: |
| Link or ring |
| Detent To Tapered End Distance: |
| Between 0.300 inches and 0.330 inches |
| Material: |
| Steel comp 631 spring or steel comp 302 spring |
| Material Specification: |
| Qq-w-423 federal specification single material response ring |
| Surface Treatment: |
| Passivate spring |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response spring |
| Style Designator: |
| Button |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| Mil-std (military Standard): |

Mil-a-8625 spec.