

View Online at <https://aerobasegroup.com/nsn/5315-01-259-0316>

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Button Handle Diameter:

1.200 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.400 inches and 0.420 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

4600 double pounds per square inch

Shoulder To Head End Distance:

0.830 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

Between 0.180 inches and 0.280 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, cl 2, type 1 federal specification 1st treatment response spindle or qq-p-416, cl 2, type 2 federal specification 2nd treatment response spindle

Style Designator:

Button

Specification Data:

26512-g+510r manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.