

View Online at <https://aerobasegroup.com/nsn/5315-01-259-7937>

Head Diameter:

Between 0.770 inches and 0.870 inches

Shank Diameter:

Between 0.6220 inches and 0.6235 inches

Ring Handle Diameter:

1.500 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.800 inches and 0.820 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

51200 double pound

Shoulder To Head End Distance:

1.250 inches

Pin Attachment Type:

Link

Detent To Tapered End Distance:

0.750 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle or cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification 1st treatment response spindle or qq-p-416, type 2, class 2 federal specification 2nd treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.