## NSN 5315-01-260-5969

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-260-5969 **Head Diameter:** 0.306 inches **Handle Length:** 2.188 inches **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 3.500 inches and 3.520 inches **Actuation Type:** Push **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.236 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** Between 0.540 inches and 0.590 inches **Special Features:** Cable required Material: Steel comp 4130 spindle **Material Specification:** Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle **Surface Treatment:** Chromium spindle **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A212a0

## NSN 5315-01-260-5969

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.