

View Online at <https://aerobasegroup.com/nsn/5315-01-260-9907>

**Head Diameter:**

Between 0.610 inches and 0.640 inches

**Shank Diameter:**

Between 0.4950 inches and 0.4980 inches

**Ring Handle Diameter:**

1.187 inches

**Detent Quantity:**

2

**Lanyard Length:**

4.000 inches

**Grip Length:**

Between 1.100 inches and 1.120 inches

**Actuation Type:**

Push

**Shear Strength:**

18400 double pounds per square inch

**Shoulder To Head End Distance:**

0.562 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.516 inches

**Material:**

Steel comp 314 shank or steel comp 303 shank or steel comp 303se shank

**Material Specification:**

Astm a 484 assn standard 1st material response shank or astm a 582 assn standard 2nd material response shank or astm a 582 federal standard 3rd material response shank

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response or qq-p-35 federal specification single treatment response

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.