

View Online at <https://aerobasegroup.com/nsn/5315-01-263-2048>

Head Diameter:

Between 0.360 inches and 0.450 inches

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Detent Quantity:

2

Lanyard Length:

Between 5.900 inches and 6.100 inches

Actuation Method:

Handle

Grip Length:

Between 2.100 inches and 2.120 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

4600 double pound

Shoulder To Head End Distance:

1.030 inches

Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.410 inches

Material:

Steel comp 4130 spindle

Material Specification:

Mil-t-6736 military specification single material response spindle or mil-s-6758 military specification single material response spindle

Surface Treatment:

Cadmium spindle and chromate spindle

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.