# NSN 5315-01-263-2049

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-263-2049

## Shank Diameter:

Between 0.2470 inches and 0.2495 inches

## **Detent Quantity:**

2

# Actuation Method:

Push button

### Grip Length:

Between 2.300 inches and 2.320 inches

#### **Actuation Type:**

Push

#### Hardness Rating:

40.0 rockwell c shank

#### Shear Strength:

9200 double pound

## Shoulder To Head End Distance:

1.550 inches

## Pin Center To Handle End Distance:

1.780 inches

## Pin Attachment Type:

Ring or hook

# **Detent To Tapered End Distance:**

0.380 inches

# Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn

standard 2nd material response spindle

## Surface Treatment:

Passivate spindle

## **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

L handle

#### **Specification Data:**

80205-nas1334 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A212a0