

View Online at <https://aerobasegroup.com/nsn/5315-01-264-0963>

**Head Diameter:**

Between 0.470 inches and 0.530 inches

**Handle Length:**

Between 1.750 inches and 2.000 inches

**Shank Diameter:**

Between 0.1870 inches and 0.1885 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 7.750 inches and 8.250 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 0.800 inches and 0.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

5150 double pound

**Shoulder To Head End Distance:**

1.550 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Steel comp 632 shank or steel comp 632 shank

**Material Specification:**

Ams 5643 assn standard single material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0