# NSN 5315-01-264-4281

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-264-4281

#### Head Diameter:

0.750 inches

### Shank Diameter:

Between 0.247 inches and 0.250 inches

# Ring Handle Diameter:

1.079 inches

#### **Detent Quantity:**

4

### **Actuation Method:**

Push button

Grip Length:

Between 0.900 inches and 0.920 inches

### Actuation Type:

Push

#### Hardness Rating:

#### 40.0 rockwell c shank

Shear Strength:

5150 double pound

### Shoulder To Head End Distance:

1.490 inches

## Pin Attachment Type:

Ring or hook

## **Detent To Tapered End Distance:**

0.380 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

### Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn

standard 2nd material response spindle

### Surface Treatment:

Passivate spindle

### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### **Style Designator:**

Ring handle

#### **Specification Data:**

80205-nas1334 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

# NSN 5315-01-264-4281

Quick Release Pin - Page 2 of 2

**Fiig:** A212a0

