NSN 5315-01-264-6056

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-264-6056

| First Find Otales |
|--|
| First End Style: |
| Chamfered |
| Second End Style: |
| Radius |
| Pinlength: |
| Between 3.740 inches and 3.760 inches |
| Pindiameter: |
| Between 1.0009 inches and 1.0011 inches |
| Second End Corner Radius: |
| Between 0.125 inches and 0.333 inches |
| First End Taper Length: |
| 0.709 inches |
| Features Provided: |
| Casehardened |
| Second End Relationship With First End: |
| Not identical |
| Hardness Rating: |
| 47.0 rockwell c and 58.0 rockwell c |
| Shear Strength: |
| 204000 double pound |
| First End Taper Angle: |
| Between 4.0 degrees and 16.0 degrees |
| Surface Finish: |
| 16.0 microinches outside diameter |
| Special Features: |
| Radius end may be chamfered 25.0 deg |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| |
| |