

View Online at <https://aerobasegroup.com/nsn/5315-01-264-6058>

**Handle Length:**

Between 2.180 inches and 3.000 inches

**Shank Diameter:**

Between 0.621 inches and 0.624 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 4.000 inches and 4.020 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

57800 double pound

**Shoulder To Head End Distance:**

2.340 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.750 inches

**Material:**

Steel comp 632 spindle or steel comp 630 spindle

**Material Specification:**

Ams 5520 assn standard 1st material response spindle or ams 5657 assn standard 1st material response spindle or ams 5643 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Specification Data:**

80205-nas1360 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0