## NSN 5315-01-264-6060

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-264-6060

First End Style:

Square

Second End Style:

Chamfered

Thread Class:

За

#### Thread Direction:

**Right-hand** 

Thread Length:

0.405 inches

Shank Length:

0.780 inches

Shoulder Width Across Flats:

0.438 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

**Overall Length:** 

2.000 inches

Second End Taper Length:

Between 0.200 inches and 0.240 inches

### Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

#### Second Shank Diameter:

Between 0.2145 inches and 0.2150 inches

#### Second End Tip Radius:

Between 0.060 inches and 0.090 inches

#### Second Shank Length:

1.095 inches

Material:

Steel comp 302 or steel comp 304 or steel comp 303se

#### Material Specification:

Qq-s-763, cond b federal specification 1st material response or qq-s-763, cond b federal specification 2nd material response or mms265,

cond b, cagec 76301 mfr ref 3rd material response

Surface Treatment:

Passivate

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

#### Style Designator:

Shoulder

#### **Thread Series Designator:**

Unjf

# NSN 5315-01-264-6060

Headless Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

