

View Online at <https://aerobasegroup.com/nsn/5315-01-265-9093>

**Handle Length:**

Between 2.250 inches and 2.500 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4995 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.500 inches and 0.520 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c shank

**Shear Strength:**

36900 double pound

**Shoulder To Head End Distance:**

1.820 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.530 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5520 assn standard 2nd material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 type 2 cl 2 federal specification single treatment response spindle

**Style Designator:**

T handle

**Specification Data:**

80205-nas1338 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0