## NSN 5315-01-266-2895

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-266-2895 **Shank Diameter:** 0.3125 inches **Button Handle Diameter:** Between 0.810 inches and 1.135 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** 1.000 inches **Actuation Type:** Push **Hardness Rating:** 40.0 rockwell c spindle **Shoulder To Head End Distance:** 0.930 inches **Criticality Code Justification:** Feat Pin Attachment Type: Link or ring **Detent To Tapered End Distance:** Between 0.300 inches and 0.330 inches **Special Features:** Tapered end diameter 0.173min-0.193max with 32.0 microinches finish and taper of 18 degrees min-22 degrees max Material: Steel comp 631 spring or steel comp 302 spring **Material Specification:** Qq-w-423, comp 302 federal specification single material response ring **Surface Treatment:** Passivate spring **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response handle or mil-a-8625, ty i military specification 2nd treatment response handle or mil-a-8625, ty ii, cls 1 military specification 2nd treatment response handle **Style Designator: Button** Shelf Life: N/a **Unit Of Measure:** 

Fiig: A212a0

No

**Demilitarization:** 

## NSN 5315-01-266-2895

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.