## NSN 5315-01-267-3028

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-267-3028 **Shank Diameter:** Between 0.3720 inches and 0.3745 inches **Detent Quantity: Actuation Method:** Handle **Grip Length:** Between 2.280 inches and 2.300 inches **Actuation Type:** Pull and push Hardness Rating: 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 18400 double pound **Shoulder To Head End Distance:** 1.730 inches Pin Center To Handle End Distance: 1.750 inches Pin Attachment Type: Hook **Detent To Tapered End Distance:** 0.510 inches Material: Steel comp 4130 shank or steel comp 4135 shank **Material Specification:** Mil-s-6758 military specification 1st material response shank or mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank **Surface Treatment:** Cadmium shank and chromate shank **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification all treatment responses shank **Style Designator:** L handle **Specification Data:** 80205-nas1356 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

A212a0

**Demilitarization:** 

## NSN 5315-01-267-3028

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.