

View Online at <https://aerobasegroup.com/nsn/5315-01-268-3466>

Head Diameter:

Between 0.630 inches and 0.800 inches

Handle Length:

Between 2.220 inches and 2.345 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

Between 5.750 inches and 6.250 inches

Actuation Method:

Push button

Grip Length:

Between 1.100 inches and 1.120 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c shank and 40.0 rockwell c shank

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.600 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0