

View Online at <https://aerobasegroup.com/nsn/5315-01-268-3466>

**Head Diameter:**

Between 0.630 inches and 0.800 inches

**Handle Length:**

Between 2.220 inches and 2.345 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 5.750 inches and 6.250 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 1.100 inches and 1.120 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.600 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0