

View Online at <https://aerobasegroup.com/nsn/5315-01-269-2689>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.630 inches

Shank Length:

0.410 inches

Shoulder Width Across Flats:

Between 0.615 inches and 0.627 inches

Shank Diameter:

Between 0.3733 inches and 0.3742 inches

Overall Length:

1.320 inches

First End Taper Length:

Between 0.046 inches and 0.076 inches

Second End Taper Length:

0.160 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

Second Shank Diameter:

Between 0.3678 inches and 0.3750 inches

First End Location:

Unthreaded end

First End Taper Angle:

Between 43.0 degrees and 47.0 degrees

Second End Tip Radius:

0.090 inches

Surface Finish:

63.0 microinches outside diameter

Second End Taper Angle:

Between 15.0 degrees and 25.0 degrees

Second Shank Length:

0.810 inches

Special Features:

Shoulder is hexagon shape

Material:

Titanium alloy uns r56400

Material Specification:

Mil-t-9047 type 3 cmp a military specification single material response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-9047 spec.