

View Online at <https://aerobasegroup.com/nsn/5315-01-270-4319>

**Head Diameter:**

Between 0.550 inches and 0.710 inches

**Shank Diameter:**

Between 0.4345 inches and 0.4360 inches

**Ring Handle Diameter:**

Between 1.090 inches and 1.348 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.100 inches and 2.120 inches

**Actuation Type:**

Push

**Shear Strength:**

25000 double pound

**Shoulder To Head End Distance:**

0.980 inches

**Pin Attachment Type:**

Link

**Detent To Tapered End Distance:**

Between 0.350 inches and 0.380 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-s-6758 military specification single material response spindle

**Surface Treatment:**

Cadmium shank and chromate shank

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses shank

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1337 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.