NSN 5315-01-270-4319

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-270-4319 **Head Diameter:** Between 0.550 inches and 0.710 inches **Shank Diameter:** Between 0.4345 inches and 0.4360 inches **Ring Handle Diameter:** Between 1.090 inches and 1.348 inches **Detent Quantity:** 2 **Actuation Method:** Push button **Grip Length:** Between 2.100 inches and 2.120 inches **Actuation Type:** Push **Shear Strength:** 25000 double pound **Shoulder To Head End Distance:** 0.980 inches Pin Attachment Type: Link **Detent To Tapered End Distance:** Between 0.350 inches and 0.380 inches Material: Steel comp 4130 spindle **Material Specification:** Mil-s-6758 military specification single material response spindle **Surface Treatment:** Cadmium shank and chromate shank **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification all treatment responses shank **Style Designator:** Ring handle **Specification Data:** 80205-nas1337 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A212a0

NSN 5315-01-270-4319

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.