

View Online at <https://aerobasegroup.com/nsn/5315-01-270-8686>

First End Style:

Chamfered

Thread Length:

2.870 inches

Shank Length:

2.000 inches

Shoulder Diameter:

Between 1.871 inches and 1.876 inches

Shank Diameter:

Between 1.432 inches and 1.442 inches

Overall Length:

5.620 inches

Undercut Width:

Between 0.060 inches and 0.090 inches

First End Taper Length:

0.130 inches

Second End Taper Length:

0.750 inches

Second End Relationship With First End:

Identical

Thread Size:

1.500 inches

Second Shank Diameter:

1.500 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Taper Angle:

15.0 degrees

Second Shank Length:

3.310 inches

Special Features:

Ballast assembly

Material:

Steel comp 4340

Material Specification:

Mil-s-5000, cond c4 or e4 military specification single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Mil-c-26074, cl 1, gr c military specification single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.