NSN 5315-01-270-8686

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-270-8686

| First End Styles |
|---|
| First End Style: |
| Chamfered |
| Thread Length: |
| 2.870 inches |
| Shank Length: |
| 2.000 inches |
| Shoulder Diameter: |
| Between 1.871 inches and 1.876 inches |
| Shank Diameter: |
| Between 1.432 inches and 1.442 inches |
| Overall Length: |
| 5.620 inches |
| Undercut Width: |
| Between 0.060 inches and 0.090 inches |
| First End Taper Length: |
| 0.130 inches |
| Second End Taper Length: |
| |
| Second End Relationship With First End: |
| |
| Thread Size: |
| 1.500 inches |
| Second Shank Diameter: |
| 1.500 inches |
| First End Location: |
| |
| First End Taper Angle: |
| 45.0 degrees |
| Second End Taper Angle: |
| 15.0 degrees |
| Second Shank Length: |
| 3.310 inches |
| Special Features: |
| Ballast assembly |
| Material: |
| Steel comp 4340 |
| Material Specification: |
| Mil-s-5000, cond c4 or e4 military specification single material response |
| Surface Treatment: |
| |
| Surface Treatment Specification: |

Mil-c-26074, cl 1, gr c military specification single treatment response

NSN 5315-01-270-8686

Headless Shoulder Pin - Page 2 of 2

Style Designator:

Undercut

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5000 spec.

