

View Online at <https://aerobasegroup.com/nsn/5315-01-271-4401>

Handle Length:

Between 2.250 inches and 2.500 inches

Shank Diameter:

Between 0.4970 inches and 0.4995 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.980 inches and 3.000 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.820 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.530 inches

Material:

Steel comp 4130 spindle

Material Specification:

Qq-a-225/5, t4 federal specification 1st material response head or qq-a-225/6, t4 federal specification 2nd material response head or qq-a-225/9, t6 federal specification 3rd material response head

Surface Treatment:

Cadmium spindle

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response shank

Style Designator:

T handle

Specification Data:

80205-nas1338 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.