NSN 5315-01-271-4401

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-271-4401 Handle Length: Between 2.250 inches and 2.500 inches **Shank Diameter:** Between 0.4970 inches and 0.4995 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 2.980 inches and 3.000 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c spindle and 40.0 rockwell c spindle **Shear Strength:** 32800 double pound **Shoulder To Head End Distance:** 1.820 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.530 inches Material: Steel comp 4130 spindle **Material Specification:** Qq-a-225/5, t4 federal specification 1st material response head or qq-a-225/6, t4 federal specification 2nd material response head or qq-a-225/9, t6 federal specification 3rd material response head **Surface Treatment:** Cadmium spindle **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response shank **Style Designator:** T handle **Specification Data:** 80205-nas1338 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A212a0

No

NSN 5315-01-271-4401

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.