## NSN 5315-01-272-8389

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-272-8389 **Shank Diameter:** Between 0.2470 inches and 0.2485 inches **Button Handle Diameter:** 1.200 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 1.500 inches and 1.520 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c shank and 40.0 rockwell c shank **Shear Strength:** 6200 double pound **Shoulder To Head End Distance:** 1.580 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel comp 4130 shank or steel comp 4135 shank **Material Specification:** Mil-s-6758 military specification 1st material response shank or mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank **Surface Treatment:** Cadmium shank and chromate shank **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response shank **Style Designator: Button Specification Data:** 80205-nas1334 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Fiig: A212a0

No

**Demilitarization:** 

## NSN 5315-01-272-8389

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.