

View Online at <https://aerobasegroup.com/nsn/5315-01-273-0856>

**First End Style:**

Round

**Second End Style:**

Square

**Shank Length:**

Between 0.625 inches and 0.719 inches

**Shoulder Diameter:**

Between 0.618 inches and 0.622 inches

**Shank Diameter:**

Between 0.618 inches and 0.622 inches

**Overall Length:**

Between 0.935 inches and 0.945 inches

**Undercut Width:**

Between 0.090 inches and 0.098 inches

**Second Undercut Width:**

Between 0.090 inches and 0.098 inches

**Second End Relationship With First End:**

Not identical

**Second Shank Diameter:**

Between 0.618 inches and 0.622 inches

**First End Location:**

Round end

**Surface Finish:**

125.0 microinches

**Second Shank Length:**

Between 0.078 inches and 0.100 inches

**Special Features:**

Pin follows standard configuration for style j162 with an extended radiused end, pin length including fully radiused end is 0.935 in. Min.-0.945 in. Max.; a 0.137 in. Min.-0.151 in. Max. Hole, 0.438 in. Max. Deep and counterbored to 0.312 in. Min.-0.328 in. Max. Is centered in the second end of the pin opposite the radiused end

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-std-171 spec.