

View Online at <https://aerobasegroup.com/nsn/5315-01-273-0856>

First End Style:

Round

Second End Style:

Square

Shank Length:

Between 0.625 inches and 0.719 inches

Shoulder Diameter:

Between 0.618 inches and 0.622 inches

Shank Diameter:

Between 0.618 inches and 0.622 inches

Overall Length:

Between 0.935 inches and 0.945 inches

Undercut Width:

Between 0.090 inches and 0.098 inches

Second Undercut Width:

Between 0.090 inches and 0.098 inches

Second End Relationship With First End:

Not identical

Second Shank Diameter:

Between 0.618 inches and 0.622 inches

First End Location:

Round end

Surface Finish:

125.0 microinches

Second Shank Length:

Between 0.078 inches and 0.100 inches

Special Features:

Pin follows standard configuration for style j162 with an extended radiused end, pin length including fully radiused end is 0.935 in. Min.-0.945 in. Max.; a 0.137 in. Min.-0.151 in. Max. Hole, 0.438 in. Max. Deep and counterbored to 0.312 in. Min.-0.328 in. Max. Is centered in the second end of the pin opposite the radiused end

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-std-171 spec.