NSN 5315-01-273-6932



Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-273-6932 First End Style: Countersunk Second End Style: Counterbored w/thru hole **Shank Length:** 0.957 inches **Shoulder Diameter:** Between 0.6869 inches and 0.6872 inches **Shank Diameter:** Between 0.6244 inches and 0.6247 inches **Overall Length:** Between 1.240 inches and 1.243 inches **Undercut Diameter:** Between 0.604 inches and 0.614 inches **Undercut Width:** 0.046 inches **Second End Counterbore Diameter:** Between 0.360 inches and 0.390 inches **Second End Counterbore Depth:** Between 0.031 inches and 0.046 inches **Second End Relationship With First End:** Not identical **Hardness Rating:** 54.0 rockwell c and 58.0 rockwell c **First End Location:** Long end First End Countersink Angle: 60.0 degrees Surface Finish: 8.0 microinches long shank First End Countersink Diameter: 0.234 inches **Special Features:** Counterbore is countersunk 0.234 inch diameter by 60 degree angle Material: Steel comp 8650h **Material Specification:** Astm a304 assn standard single material response

Style Designator: Undercut

Shelf Life:

N/a

NSN 5315-01-273-6932

Headless Shoulder Pin - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A212a0