

View Online at <https://aerobasegroup.com/nsn/5315-01-276-3480>

**Head Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3745 inches

**Ring Handle Diameter:**

1.060 inches

**Detent Quantity:**

4

**Actuation Method:**

Push button

**Grip Length:**

Between 1.400 inches and 1.420 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

36.0 rockwell c shank and 40.0 rockwell c shank

**Shear Strength:**

18400 double pound

**Shoulder To Head End Distance:**

1.730 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

0.510 inches

**Material:**

Steel comp 4130 shank or steel comp 4135 shank

**Material Specification:**

Mil-s-6758 military specification 1st material response shank or mil-t-6736 military specification 1st material response shank or mil-t-6735 military specification 2nd material response shank

**Surface Treatment:**

Cadmium shank and chromate shank

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response shank

**Style Designator:**

Ring handle

**Specification Data:**

80205-nas1356 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.